


fork lever
ITEM #.: 0
MAT'L.:
HRD.:
REQ'D.:
FINISH:

- NOTE:
- RADIUS ALL EDGES .010-.015 UNLESS OTHERWISE NOTED
 - STAMP ALL INS & OUTS (PER DWG.)
 - STAMP ALL PARTS WITH PART#, STEEL TYPE, AND HARDNESS
 - STAMP MOLD ON BOTH SIDES (OPERATOR & TOP)
MOLD#
MOLD WEIGHT: LBS.
 - BREAK FRAME PLATE EDGES 1/16 X 45°
 - MOLDING SURFACE FINISH SPI-SPE B-3 OR BETTER UNLESS OTHERWISE SPECIFIED
 - UNLESS SPECIFIED ORDINATE DIMENSIONS ARE TYPICAL
 - ADD PRY SLOTS AND CLEAN OUTS TO SUIT
 - (*) THIS SYMBOL DENOTES CRITICAL DIMS PER CUSTOMER DWG. # OF CRITICAL DIMS =
 - UNLESS OTHERWISE SPECIFIED ALL DIMS IN "in"


CAVALLERO PLASTICS INC.
 1250 NORTH ST. PHONE 413-443-0925
 PITTSFIELD MA 01201 FAX 413-443-9586
 E-mail sales@cplas.com

TOLERANCE UNLESS SPECIFIED OTHERWISE INCHES					PART NAME:	
.XXXX	.XXX	.XX	.X & FRAC.	ANGLES	fork lever	
± .0002	± .001	± .005	± .12	± .25°	MOLD #	JOB #
MILLIMETERS					SIZE C	DWG #
± .130	± .40	± 3.0		DRAWING BY:	APPROVED BY:	SCALE: 2:1
DATE: 1/12/2016				DATE:	SHEET: 1 OF 1	
					REV	